

Round flow cassette

FWC-BT/BF



BLDC fan motor unit for ceiling mounting. 360° air discharge

- › 360° air discharge ensures uniform air flow and temperature distribution
- › Modern style decoration panel in white (RAL9010)
- › Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- › Comfortable horizontal air discharge ensures draughtfree operation and prevents ceiling soiling
- › Possibility to shut 1 or 2 flaps for easy installation in corners


FWC-BT/BF



FWC-BT/BF				06	07	08	09	06	07	08	09
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Super high	kW	5.8	6.8	7.7	8.7	5.8	6.6	7.6	8.7
		High	kW	5.0	5.6	6.3	7.2	4.9	5.6	6.3	7.2
		Low	kW	4.1	4.7	4.9	5.7	4.0	4.6	4.8	5.7
	Sensible capacity	Super high	kW	4.1	4.7	5.6	6.5	4.1	4.7	5.6	6.5
		High	kW	3.4	4.0	4.5	5.3	3.4	3.9	4.4	5.2
		Low	kW	2.8	3.3	3.5	4.1	2.7	3.2	3.4	4.0
Heating capacity	2-Pipe	Super high	kW	8.0	8.9	10.6	12.1	-			
		High	kW	6.3	7.1	8.3	9.5	-			
		Low	kW	5.5	5.9	6.9	7.8	-			
	4-Pipe	Super high	kW	-				7.5	8.4	9.7	11.0
		High	kW	-				6.2	6.8	7.8	8.8
		Low	kW	-				5.5	5.9	6.7	7.8
Power input	Super high	W	45	54	77	107	46	55	77	107	
	High	W	40	46	58	76	41	47	59	77	
	Low	W	34	37	39	45	35	38	40	46	
Dimensions	Unit	Height	mm	288							
		Width	mm	840							
		Depth	mm	840							
Weight	Unit	kg	26				29				
	Type		Turbo fan								
Fan	Quantity		1								
	Air flow rate	High	m³/h	1,062	1,236	1,518	1,776	1,032	1,200	1,476	1,746
		Low	m³/h	720	840	888	1,044	684	804	852	1,014
Sound power level	Super high	dB(A)	43	47	53	57	43	47	53	57	
	High	dB(A)	36	39	44	49	36	39	44	49	
Sound pressure level	Super high	dB(A)	29	33	39	43	29	33	39	43	
	High	dB(A)	24	28	32	37	24	28	32	37	
Piping connections	Drain	OD	VP25 (External dia.32 / internal dia. 25)								
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240								
Control systems	Infrared remote control		BRC7E532F / BRC7E533F								
	Wired remote control		BRC315D7								

(l) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-483 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.